

PRELIMINARY SPEC SHEET

Diesel Generator Set – 2,750 kW – 60 Hz



C175-16 Standby 2,750 kW / 3,438 kVA- 60 Hz – 1800 RPM 480 and 4,160 Volts

<i>System</i>	<i>Standard</i>
Air Inlet	<ul style="list-style-type: none">• Single element canister type air cleaners• Service indicator
Cooling	<ul style="list-style-type: none">• Radiator with guard (43°C ambient temperature)• Coolant drain line with valve• Caterpillar Extended Life Coolant
Exhaust	<ul style="list-style-type: none">• Dry exhaust manifold• Flanged faced outlets (ANSI / DIN)
Fuel	<ul style="list-style-type: none">• Secondary fuel filters• Fuel priming pump• Flexible fuel lines• Fuel cooler (optional)
Generator	<ul style="list-style-type: none">• IE (LV) and PMG (MV, HV)• Class H insulation• Class H temperature (150°C rise)• CDVR voltage regulator• Reactive droop• Bus bar connections• Winding temperature sensors std PM @ 480 Volt (opt for LV)• Anti-condensation space heaters (opt for LV)• Bearing temperature sensors – option (opt for LV)
Governing System	<ul style="list-style-type: none">• Caterpillar ADEM™ A4 speed control governor
Control Panels	<ul style="list-style-type: none">• EMCP 3 (package mounted)
Lube System	<ul style="list-style-type: none">• Lubricating oil and filter• Oil drain line with valves• Fumes disposal• Gear type lube oil pump
Mounting	<ul style="list-style-type: none">• Rubber, anti-vibration mounts (shipped loose)
Starting/Charging	<ul style="list-style-type: none">• 24 Volt starting motor(s)• 45 Amp charging alternator• Batteries with rack and cables• Battery disconnect switch
General	<ul style="list-style-type: none">• Right-hand service• Paint – Caterpillar Yellow except rails and radiators gloss black• SAE standard rotation• Flywheel and flywheel housing – SAE No. 0
Note	For any additional options, consult the factory

PRELIMINARY

1 of 4

1/5/2006

Information contained in this publication may be considered confidential.

www.cat-ElectricPower.com

Discretion is recommended when distributing.

Materials and specifications are subject to change without notice.

CAT, CATERPILLAR, their respective logos and “Caterpillar Yellow”, as well as corporate and product Identify used herein, are trademarks of Caterpillar and may not be used without permission.

© 2005 Caterpillar
All Rights Reserved.
Printed in U.S.A.

PRELIMINARY SPEC SHEET

Diesel Generator Set – 2,750 kW – 60 Hz



Specifications

CAT Generator

ExcitationIE
Pitch.....2/3
Number of poles 4
Number of bearings 2
Insulation UL 1446 Recognized Class H
IP rating Drip Proof IP23
Alignment closed coupled
Overspeed capability - % of rated 125
Wave form Less than 5% deviation
Paralleling kit/Droop transformer Standard
Telephone Influence Factor Less than 50
Harmonic distortion Less than 5%

CAT Digital Voltage Regulator

Microprocessor based
VAR/PF control Standard
Direct 3 Phase sensing with selectable volts/Hz
Communicates with EMCP 3
Programmable operating characteristics
Voltage regulation ... Less than +/- 0.25% (steady state), Less than +/- 1% (no load to full load)
Compatible with self-excited, PMG, and IE

CAT Diesel Engine

C175-16, 4-stroke-cycle water-cooled diesel
Bore – mm 175 mm (6.89 in)
Stroke – mm 220 mm (8.66 in)
Displacement – L 84.6 L (5165.1 cu. in)
Compression ratio 16.7:1
Aspiration SCAC
Fuel system Common Rail
Governor type Caterpillar ADEM™ A4

CAT EMCP3 Control Panels

- EMCP 3.1 (Standard)
- EMCP 3.2 & 3.3 (Optional)
- 24 Volt DC control
- Generator instruments designed to meet UL/CSA/CE/
- Integral generator terminal box
- Single location for customer connection
- MODBUS isolated data link (RS-485 half-duplex) supports serial communication at data rate up to 115.2 up to 56 kbaud
- Auto start/stop control
- True RMS metering, 3-phase
- Digital indication for:
 - RPM
 - Operating hours
 - Oil pressure
 - Coolant temperature
 - System DC volts
 - L-L Volts, L-N Volts, phase amps, Hz
 - kW, kVA, kVAR, kW-hr, %kW, PF
- Programmable protective relay functions:
 - Under and over voltage
 - Under and over frequency
 - Reverse power
 - Overcurrent

CAT Control Options

- Programmable annunciator (local and remote or both) (3 max)
- Spare discrete I/O (12 in/8 out) (2 max)
- Generator temperature monitor/protection (stator & bearing)
- Engine temperature monitor/protection

PRELIMINARY

2 of 4

1/5/2006

Information contained in this publication may be considered confidential.
Discretion is recommended when distributing.

www.cat-ElectricPower.com

Materials and specifications are subject to change without notice.
CAT, CATERPILLAR, their respective logos and “Caterpillar Yellow”, as well as corporate and product
Identify used herein, are trademarks of Caterpillar and may not be used without permission.

© 2005 Caterpillar
All Rights Reserved.
Printed in U.S.A.

PRELIMINARY SPEC SHEET



Diesel Generator Set – 2,750 ekW – 60 Hz

Generator Set Technical Data

C175-16, 60Hz, 1800 RPM	Standby – EPA Tier 2		Standby – Low BSFC	
Package Performance Genset Power rating with fan Genset Power rating @ 0.8 pf	2,750 ekW 3,438 kVA		2,750 ekW 3,438 kVA	
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	728.7 L/hr 529.3 L/hr 410.4 L/hr	192.5 Gal/hr 139.8 Gal/hr 108.4 Gal/hr	728.7 L/hr 507.7 L/hr 358.2 L/hr	192.5 Gal/hr 134.1 Gal/hr 94.6 Gal/hr
Cooling System Radiator air flow rate @ 0.25 external static restriction	3602.2 m ³ /min	127,212 cfm	3602.2 m ³ /min	127,212 cfm
Inlet Air Combustion air inlet flow rate	259 m ³ /min	9,146.5 cfm	259 m ³ /min	9,146.5 cfm
Exhaust System Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	424°C 604 m ³ /min 355.6 mm 5 kPa	795°F 21,330.1 cfm 14 in. 20 in. H ₂ O	424°C 604 m ³ /min 355.6 mm 5 kPa	795°F 21,330.1 cfm 14 in. 20 in. H ₂ O
Heat Rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine	1,682.1 kW 2,431.2 kW 398.6 kW 77.01 kW	95,746.8 Btu/min 138,380.8 Btu/min 22,690.5 Btu/min 4,383.4 Btu/min	1,682.1 kW 2,431.2 kW 398.6 kW 77.01 kW	95,746.8 Btu/min 138,380.8 Btu/min 22,690.5 Btu/min 4,383.4 Btu/min
Noise Exhaust Sound Data: 23.0 Feet @ 100% Load Mechanical Sound Data: 23.0 Feet @ 100% Load	Overall Sound DB(A) 105.4 Overall Sound DB(A) 101.4		Overall Sound DB(A) 105.4 Overall Sound DB(A) 101.4	
Emissions (Estimate Nominal) NOx g/hp-hr HC g/hp-hr CO g/hp-hr PM g/hp-hr	<u>@ EPA Tier 2</u> 4.8 g/hp-hr (Nox + NMHC) n/a g/hp-hr 2.6 g/hp-hr 0.15 g/hp-hr		<u>@ rated performance</u> 4.89 g/hp-hr 0.12 g/hp-hr 0.55 g/hp-hr n/a g/hp-hr	

Ambient capability at 750 m (2,461 ft) @ 43°C above sea level. For ambient capability at other altitudes, consult the Caterpillar factory.

Preliminary Package Dimensions without Radiator

1820 Frame Package Dimensions		
Length	5,784.8 mm	232.1 in
Width	1,650.5 mm	65.0 in
Height	2,248.5 mm	88.5 in
Weight	18,200 kg	40,125 lbs

Note: Do not use for installation design.
Consult factory for final configuration.

1840 Frame Package Dimensions		
Length	5,894.8 mm	232.1 in
Width	1,650.5 mm	65.0 in
Height	2,248.5 mm	88.5 in
Weight	18,200 kg	40,125 lbs

Note: Do not use for installation design.
Consult factory for final configuration.

Materials and specifications are subject to change without notice.

PRELIMINARY

3 of 4

1/5/2006

Information contained in this publication may be considered confidential.

www.cat-ElectricPower.com

Discretion is recommended when distributing.

Materials and specifications are subject to change without notice.

CAT, CATERPILLAR, their respective logos and “Caterpillar Yellow”, as well as corporate and product Identify used herein, are trademarks of Caterpillar and may not be used without permission.

© 2005 Caterpillar
All Rights Reserved.
Printed in U.S.A.

PRELIMINARY SPEC SHEET

Diesel Generator Set – 2,750 kW – 60 Hz

Generator Technical Data



C175-16, Standby, 60Hz, 1800 RPM	480 Volts (std)	480 Volts (opt)	4,160 Volts (opt)
Heat Rejection Heat rejection to atmosphere from generator	93.85 kW 5,341.9 Btu/min	90.91 kW 5,174.6 Btu/min	93.85 kW 5,341.9 Btu/min
Generator Motor starting capability @32.5% voltage dip, 0.4 PF	7892 skVA	8660 skVA	7859 skVA
Frame	1824	1844	1824
Winding	Random	Form	Form
Temperature Rise	150°C 302°F	150°C 302°F	150°C 302°F

Generator temperature rise is based on a 40°C ambient per NEMA MG1-32.

Preliminary Horizontal Radiator Dimensions

	43°C Radiator	
Length	4,714.2 mm	185.6 in
Width	2,279.7 mm	89.75 in
Height	2,561.8 mm	100.86 in
Weight	5,102 kg	11,248 lbs

Note: Do not use for installation design.
Consult factory for final configuration.

Materials and specifications are subject to change without notice.

Rating Definitions and Conditions

Meets or Exceeds International Specifications: ABGSM TM3, AS1359, AS2789, BS4999, BS5000, BS5514, DIN6271, DIN6280, EGSA101P, IEC34/1, ISO3046/1, ISO8528, JEM1359, NEMA MG 1-32

Ratings are based on SAE J1995 standard conditions. These ratings also apply at ISO3046/1, DIN6271, and BS5514 standard conditions.

Fuel rates are based on fuel oil of 35° API (16°C or 60°F) gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29°C (85°F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.)

PRELIMINARY

4 of 4

1/5/2006

Information contained in this publication may be considered confidential.

www.cat-ElectricPower.com

Discretion is recommended when distributing.

Materials and specifications are subject to change without notice.

© 2005 Caterpillar

CAT, CATERPILLAR, their respective logos and “Caterpillar Yellow”, as well as corporate and product Identify used herein, are trademarks of Caterpillar and may not be used without permission.

All Rights Reserved.
Printed in U.S.A.