


Exclusively from your Caterpillar® dealer



STANDBY 30-50 kW
PRIME 27-42.5 kW
60 Hz

Model	Standby — kW (kVA)		Prime — kW (kVA)	
	LP	Natural	LP	Natural
G30F3	30 (37.5)	30 (37.5)	27 (33.8)	27 (33.8)
G40F3	40 (50)	40 (50)	36 (45)	36 (45)
G50F3	50 (62.5)	45 (56.3)	42.5 (53.1)	37.5 (46.9)
G30F3S	30 (30)	30 (30)	27 (27)	27 (27)
G35F3S	35 (35)	35 (35)	31.5 (31.5)	31.5 (31.5)
G45F3S	45 (45)	42.5 (42.5)	40 (40)	36 (36)

FEATURES

GENERATOR SET

- Complete system designed and built at ISO 9001 certified facilities
- Factory tested to design specifications at full load conditions

ENGINE

- Governor, Isochronous Woodward electronic
- Electrical system, 12 VDC
- Cartridge type filters
- Battery, rack and cables
- Coolant and lube oil drains piped to edge of base

GENERATOR

- Insulation system, class H
- Drip proof generator air intake (NEMA 2, IP23)
- Electrical design in accordance with BS5000 Part 99, IEC60034-1, EN61000-6, NEMA MG-1.33

AUTOMATIC VOLTAGE REGULATOR

- Voltage within $\pm 0.5\%$ 3 Phase and $\pm 1.0\%$ Single Phase at steady state from no load to full load
- Provides fast recovery from transient load changes

COOLING SYSTEM

- Radiator and cooling fan complete with protective guards
- Standard ambient temperatures up to 131° F (55° C)

MOUNTING ARRANGEMENT

- Heavy-duty fabricated steel base with lifting points
- Anti-vibration pads to ensure vibration isolation
- Complete OSHA guarding
- Stub-up pipe ready for connection to silencer pipework
- Weather protective enclosures are available
- Flexible fuel lines to base with NPT connections

CIRCUIT BREAKER

- UL/CSA listed
- 3-pole with solid neutral
- NEMA 1 steel enclosure, vibration isolated
- Electrical stub-up area directly below circuit breaker

CONTROL SYSTEM

- 2001 Autostart control panel
- Vibration isolated NEMA 1 enclosure with lockable hinged door
- AC and DC wiring looms

EQUIPMENT FINISH

- All electroplated hardware
- Anticorrosive protection prior to painting
- High gloss polyurethane paint for durability and scuff resistance

QUALITY STANDARDS

- BS4999, BS5000, BS5514, EN61000-6, NEMA MG1-33, NFPA 110 (with optional equipment)

DOCUMENTATION

- Operation and maintenance manuals provided
- Wiring diagrams included

WARRANTY

- All equipment carries full manufacturer's warranty

STANDBY 30 - 50 kW
PRIME 27 - 42.5 kW
60 Hz

OLYMPIAN™

Exclusively from your Caterpillar® dealer

OPTIONAL EQUIPMENT*

ENCLOSURE

- Weatherproof enclosure (includes internal silencer system)
- Sound attenuated enclosure (includes internal silencer system)
- Panel viewing window
- External emergency stop pushbutton

SILENCER SYSTEM — OPEN UNIT

- Level 1 silencer
- Level 2 silencer
- Level 3 silencer
- Mounting kit
- Through-wall installation kits

ENGINE

- Battery heater
- Lube oil drain pump
- Lube oil sump heater

CIRCUIT BREAKER

- Auxiliary voltfree contacts
- Shunt trip (100+ amp breakers)

GENERATOR

- Anti-condensation heater
- AREP excitation system (3-Phase only)
- Generator upgrade 1 size (3-Phase only)
- Permanent magnet generator (except G30F3)

COOLING SYSTEM

- Coolant heater
- Low coolant temperature alarm
- Low coolant level shutdown
- Radiator transition flange

MOUNTING ACCESSORIES

- Seismic (Zone 4) vibration isolators

*Some options may not be available on all models. Not all options are listed.

CONTROL SYSTEM

- Control Panel Removal, AC and DC wiring looms terminated in sockets
- 4001 Autostart control panel
- 4001E Autostart control panel

FUEL SYSTEM

- LP gas (vapor)
- LP gas (liquid)
- Natural gas/LP gas (vapor) automatic changeover
- Natural gas/LP gas (liquid) automatic changeover
- Low gas pressure alarm

REMOTE ANNUNCIATORS

- 8- and 16-channel remote annunciator panel (supplied loose)
- Remote annunciator upgrade normal/run control switch
- Remote annunciator upgrade lockdown emergency stop button

MISCELLANEOUS ACCESSORIES

- Toolkit
- Additional operator's manual pack
- Special enclosure color
- UL listing / CSA certification
- French Language labels


EXTENDED SERVICE CONTRACTS

- Extended Service Coverage available

TESTING

- Factory witness test (restricted to 6 hours — full load, 1.0 pf)

GENERATOR SET DIMENSIONS AND WEIGHTS



Model	Length in (mm)	Width in (mm)	Height in (mm)	Weight lbs (kg)**
G30F3	86.6 (2200)	39.4 (1000)	47.5 (1206)	1422 (645)
G40F3	86.6 (2200)	39.4 (1000)	47.5 (1206)	1543 (700)
G50F3	86.6 (2200)	39.4 (1000)	47.5 (1206)	1698 (770)
G30F3S	86.6 (2200)	39.4 (1000)	47.5 (1206)	1543 (700)
G35F3S	86.6 (2200)	39.4 (1000)	47.5 (1206)	1587 (720)
G45F3S	86.6 (2200)	39.4 (1000)	47.5 (1206)	1698 (770)

NOTE: General configuration not to be used for installation. See specific dimensional drawings for detail.

**Includes oil and coolant

STANDBY 30 - 50 kW
PRIME 27 - 42.5 kW
60 Hz

OLYMPIAN™

Exclusively from your Caterpillar® dealer

SPECIFICATIONS



GENERATOR

Voltage Regulation... ±0.5% 3 Phase and 1.0 % Single
 Phase at steady state from no load to full load
 Frequency ±0.25% for constant load,
 no load to full load
 Waveform Distortion THD less than 4%,
 Radio Interference Compliance with BS800 and
 VDE Class G&N
 Telephone Influence Factor TIF <50
 per NEMA MG 1-32.11
 Telephone Harmonic Factor THF <2%
 Stator 2/3 pitch
 Type Brushless, self excited, self-regulated,
 drip proof, 4-pole, sealed bearings,
 direct coupled by flexible disk,
 12 reconnectable leads
 Insulation Class H per NEMA MG1-1.66
 Temperature Rise Within Class H limits
 Overspeed Capability 125%
 Available Voltages 1-Phase — 120/240,
 110/220
 3-Phase — 277/480, 120/240,
 120/208,
 Deration Please consult factory
 for available outputs
 Ratings At 77° F (25° C), 500 ft. (152.4 m),
 60% humidity, 1.0 pf (1-Phase),
 0.8 pf (3-Phase)



ENGINE

Manufacturer Ford Motor Co.
 Model ESG642
 Type 4-Cycle
 Aspiration Natural
 Cylinder Configuration V6

Displacement — cu in (L) 256 (4.2)
 Bore — in (mm) 3.81 (96.8)
 Stroke — in (mm) 3.74 (95.0)
 Compression Ratio 9.3:1
 Governor
 Type Electronic
 Class A1

Piston Speed — ft/sec (m/sec) 18.7 (5.7)
 Air Cleaner Type Dry, light duty

LP Gas

Engine Speed — rpm 1800
 Max Power at Rated rpm — hp (kW)
 Standby 77.4 (57.8)
 Prime 66.2 (49.4)
 BMEP — psi (kPa)
 Standby 133.2 (918)
 Prime 114 (786)

Natural Gas

Engine Speed — rpm 1800
 Max Power at Rated rpm — hp (kW)
 Standby 69.6 (51.9)
 Prime 59.4 (44.3)
 BMEP — psi (kPa)
 Standby 119.8 (826)
 Prime 102.2 (705)



CONTROL PANEL

NEMA 1 steel enclosure with lockable hinged door
 Vibration isolated mounted Autostart control panel
 Single location customer connector point
 Electrical stub-up area directly below control panel

RATING DEFINITIONS

Standby — Applicable for supplying continuous electrical power (at variable load) in the event of a utility power failure. No overload is permitted on these ratings. The generator is peak rated (as defined in ISO8528-3).

Prime — Applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and the generator set can supply 10 percent overload power for 1 hour in 12 hours.

Consult your Olympian representative for more information.

www.CAT-ElectricPower.com

© 2005 Caterpillar
 All rights reserved.
 Printed in U.S.A.

STANDBY 30/30 kW
PRIME 27/27 kW
60 Hz

OLYMPIAN™

Exclusively from your Caterpillar® dealer

G30F3 (3-Phase)

Materials and specifications are subject to change without notice.

Generator Set Technical Data — 1800 rpm/60 Hz		LP Gas		Natural Gas	
		Standby	Prime	Standby	Prime
Power Rating	kW (kVA)	30.0 (37.5)	27.0 (33.8)	30.0 (37.5)	27.0 (33.8)
Lubricating System Type: Full Pressure Oil Filter: Spin-On, Full Flow Oil Type Required: API CF-4 Total Oil Capacity Oil Pan	U.S. gal (L) U.S. gal (L)	1.5 (5.7) 1.2 (4.7)	1.5 (5.7) 1.2 (4.7)	1.5 (5.7) 1.2 (4.7)	1.5 (5.7) 1.2 (4.7)
Fuel System Generator Set Fuel Consumption 100% Load 75% Load 50% Load	Cfh (m³/hr) Cfh (m³/hr) Cfh (m³/hr)	164 (4.7) 124 (3.5) 85 (2.4)	147 (4.2) 112 (3.2) 74 (2.1)	454 (12.9) 345 (9.8) 236 (6.7)	410 (11.6) 306 (8.7) 204 (5.8)
Engine Electrical System Ignition System: Electronic, Distributorless Voltage/Ground: 12/Negative Battery Charging Generator Ampere Rating	Amps	95	95	95	95
Cooling System Water Pump Type: Centrifugal Radiator System Capacity Incl. Engine Maximum Coolant Static Head Coolant Flow Rate Minimum Water Temperature to Engine Temperature Rise Across Engine (Air) Heat Rejected to Coolant at Rated Power Total Heat Radiated to Room at Rated Power Radiator Fan Load	U.S. gal (L) Ft H ₂ O (m H ₂ O) U.S. gal/hr (L/min) °F (°C) °F (°C) Btu/min (kW) Btu/min (kW) Hp (kW)	5.3 (20) 32.4 (9.8) 1236 (79.5) 169 (76) 9 (5) 1182 (20.8) 932 (16.4) 1.88 (1.4)	5.3 (20) 32.4 (9.8) 1236 (79.5) 169 (76) 9 (5) 1069 (18.8) 847 (14.9) 1.88 (1.4)	5.3 (20) 32.4 (9.8) 1236 (79.5) 169 (76) 9 (5) 1182 (20.8) 932 (16.4) 1.88 (1.4)	5.3 (20) 32.4 (9.8) 1236 (79.5) 169 (76) 9 (5) 1069 (18.8) 847 (14.9) 1.88 (1.4)
Air Requirements Combustion Air Flow Maximum Air Cleaner Restriction Radiator Cooling Air (zero restriction) Generator Cooling Air Allowable Air Flow Restriction (After radiator) Cooling Airflow (@ rated speed) Rate with restriction	Cfm (m³/min) In H ₂ O (kPa) Cfm (m³/min) Cfm (m³/min) In H ₂ O (kPa) Cfm (m³/min)	53 (1.5) 10.1 (2.5) 6356 (180) 381 (10.8) 0.5 (0.125) 4238 (120)	50 (1.4) 10.1 (2.5) 6356 (180) 381 (10.8) 0.5 (0.125) 4238 (120)	53 (1.5) 10.1 (2.5) 6356 (180) 381 (10.8) 0.5 (0.125) 4238 (120)	50 (1.4) 10.1 (2.5) 6356 (180) 381 (10.8) 0.5 (0.125) 4238 (120)
Exhaust System Maximum Allowable Backpressure Exhaust Flow at Rated kW Exhaust Temperature at Rated kW — Dry Exhaust	In Hg (kPa) Cfm (m³/min) °F (°C)	4.5 (15.3) 141 (4) 1080 (584)	4.5 (15.3) 131 (3.7) 1054 (570)	4.5 (15.3) 141 (4) 1080 (584)	4.5 (15.3) 131 (3.7) 1054 (570)
Generator Set Noise Rating* (Without Attenuation) at 3 ft (1 m)	dB(A)	88	88	88	88

Generator Technical Data	277/480V	120/240V	120/208V
Motor Starting Capability: (kVA) (30% Voltage Dip)			
Self Excited	72	54	54
AREP Excited	85	64	64
Full Load Efficiencies (LPG):			
Standby	90.1	89.0	89.0
Prime	90.4	89.5	89.5
Reactances (per unit):			
X _d	2.21	2.94	2.94
X' _d	0.12	0.16	0.16
X'' _d	0.058	0.078	0.078
X _q	1.10	1.47	1.47
X'' _q	0.083	0.110	0.110
X ₂	0.071	0.094	0.094
X ₀	0.006	0.007	0.006
Time Constants:	t' _d 25 ms	t'' _d 2.5 ms	t' _{do} 469 ms
			t _a 4 ms

* dB(A) levels are for guidance only