



CABINET INTERCONNECTIONS

QTY	SYM	TYPE	NOTES
3	A	BUSS BAR	SUPPLIED
2	B	4/0 X-FLEX, 2 PER PHASE & GROUND #10, 1 PER NEUTRAL	SUPPLIED
1	C	24-12 AWG (2 EA, TWISTED PAIRS); CAT5, 4 PAIR UTP-24 AWG (3 EACH) 9-WIRE SERIAL CABLE; PHONE CABLE	SUPPLIED
1	D	CUSTOMER INTERFACE 24-12 AWG EPD-4 WIRES, INPUT CONTACTS-12 WIRES, OUTPUT CONTACTS-18 WIRES, RJ45 6-PIN (MODEM) RJ45 8-PIN (NETWORK) DB9 (SERIAL)	(OPTIONAL) CUSTOMER SUPPLIED
1	E	BUSS BAR (PHASES) AND 2 EACH 4/0 X-FLEX (NEUTRAL)	SUPPLIED
1	F	4/0 X-FLEX, 2 NEUTRAL	SUPPLIED

1E2B40 SUPPLIER REPRINT
 1E2733 DRAWING - AUTOCAD
 B1E0011 INTRP & TUL

DATE: 05/01/01
 DESIGNED BY: J. THURN
 CHECKED BY: J. THURN
 APPROVED BY: J. THURN

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES
 DIMENSIONS IN PARENTHESIS ARE BASED ON
 SCALE: NONE

SCALE: NONE
 SHEET 00 OF 01 DATE: 05MAY01

CATERPILLAR INC.
 THE INFORMATION HEREON IS THE PROPERTY OF CATERPILLAR INC. AND IS TO BE USED ONLY FOR THE SPECIFIC PROJECT AND FOR WHICH IT IS ISSUED. NO PARTS OR INFORMATION FROM THIS DRAWING IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.
 (CUPS 300X4 WIRE)

209-6778