



CABINET INTERCONNECTIONS			
QTY	SYM	TYPE	NOTES
2	A	BUSS BAR	SUPPLIED
6	B	4/0 X-FLEX, 2 PER PHASE & GROUND #10, 1 PER NEUTRAL	SUPPLIED
3	C	24-12 AWG (2 EA, TWISTED PAIRS), CAT5, 4 PAIR UTP-24 AWG (3 EACH), 9-WIRE SERIAL CABLE, PHONE CABLE	SUPPLIED
2	D	CATS, 4 PAIR UTP-24 AWG (2 EACH)	SUPPLIED
1	E	CUSTOMER INTERFACE 24-12 AWG EPD-4 WIRES, INPUT CONTACTS-12 WIRES, OUTPUT CONTACTS-18 WIRES RJ45 6-PIN (MODEM) RJ45 8-PIN (NETWORK) DB9 (SERIAL)	(OPTIONAL) CUSTOMER SUPPLIED
1	F	BUSS BAR (PHASES) AND 2 EACH 4/0 X-FLEX (NEUTRAL)	SUPPLIED
1	G	4/0 X-FLEX, 2 PER NEUTRAL	SUPPLIED

1E2B40 SUPPLIER REPRINT	
1E2733 DRAWING - AUTOCAD	
1E0011 INTRP & TUL	
1	PRICE NO.
DRN: TI MATHEWS	
CHK: GM WILLIAMS	
APPR: RF THURN	
0001	EXP: 10/01
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES DIMENSIONS IN 1/8" AND 3/16" ARE BASED ON	
1	SCALE: NONE
1	THIS ANGLE
1	DATE
00	1B MAY 01
CATERPILLAR INC.	
THE INFORMATION HEREON IS THE PROPERTY OF CATERPILLAR INC. AND IS TO BE USED ONLY FOR THE SPECIFIC PROJECT AND NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.	
HYDARAM-GUNNINGTON (UPS 900X4 WIRE)	
209-6782	
1	CONTROL
1	W866